



## SuperPrint 840-440 13oz Matte

Item	Unit	Value	Test Method
<b>Base Fabric</b>	Denier	840DX840D	(High tenacity yarn) 100% PES
<b>Construction</b>	Weaving/inch	9x9	/
<b>Weight of fabric</b>	Gsm/m2	75±5	DIN53352 BS3424 Method5B
<b>Weight of PVC</b>	Gsm/m2	365±5	DIN53352 BS3424 Method5B
<b>Total weight</b>	Gsm/m2	440±10	DIN53352 BS3424 Method5A
<b>Thickness</b>	mm	0.33±0.02	DIN EN ISO 2286-3
<b>Width</b>	cm	Up to 510	/
<b>Tensile Strength</b>	N/5cm	Warp	1350
		Weft	1200
<b>Tearing Strength</b>	N	Warp	125
		Weft	100
<b>Adhesion</b>	N/5CM	60	DIN53357 BS3425 Method9B
<b>Temperature Resistance</b>	°C	-20~70	DIN53357 BS3425 Method10
<b>Lacquering</b>	None		
<b>Flammability</b>	None		
<b>LOW CADMIUM &amp; HEAVY METALS</b>	Cadmium free		
<b>Conclusions and Announcements</b>	The technical data on this page is calculated on average, and ±5% tolerance is acceptable		

INGREDIENT	CONTENT
Polyester	13%
PVC Resin	43.50%
DOP	15.20%
CaCO <sub>3</sub>	25.17%
Stabilizer	1.83%
Plasticizer and Else	1.30%