

## # HOME STAGING

# STN 703 TRANSLUCENT STONES

### INDOOR INSTALLATION



Natural stone surface reinforced with polyester resin and allowing light to pass through, giving it a translucent hue.







**Durability:** 12 to 15 years for a vertical application in Central Europe.



**Use:** interior decoration plates for all types of smooth non-porous surfaces, etc.



**Maintenance:** after 30 days with a usual cleaning solution (non abrasive, without ammonia...). Cleaning products that could scratch are not recommended.



**Storage:** 2 years from delivery. This film must be stored away from excessive humidity and sunlight, at a temperature below 38°C.

In order to meet high standards, we recommend that you do not mix films from different productions

#### **INFORMATION**

**SUPPORT:** Natural stone reinforced with polyester resin

THICKNESS: 2 mm
COLORS: Olive brown, chalk, charcoal grey
APPLICATION SIDE: Internal
RESISTANCE: Optimale
NORMES: EUROCLASSES
GUARANTEE: 10 years\*

\* For glazing not exposed to the sun

#### **DIMENSIONS**

Per unit:

1,22 x 0,6 m

Application Note





Video of the installation





#### Method of application

The surface to be bonded must be free of dust, grease or any other contaminant. Some materials such as polycarbonate can cause bubbling problems. A compatibility test is therefore recommended. Possibility to install on plexiglass and polycarbonate.

#### Production monitoring and standards

In order to constantly improve our productions, we may have to modify without notice the colors and manufacturing processes. We recommend to our users, before applying our films, to make sure that they are exactly suitable for the intended use and to comply with the standards in force.